

HL-E und HL-A Reinigungszeiten für Hochdruckkanzen

Spritzkopf-Typ	Umdrehungen für kompletten Ablauf	Überlappung mit 2 Düsen / Spritzkopf	Elektromotor 50 Hz				Elektromotor 60 Hz			
			11 min-1	17 min-1	24 min-1	33 min-1	13 min-1	20 min-1	19 min-1	40 min-1
R-32	33	5.45°	03'00"	01'56"	01'23"	01'00"	02'32"	01'39"	01'44"	00'50"
RK-37	37	4.86°	03'22"	02'11"	01'33"	01'07"	02'51"	01'51"	01'57"	00'56"
R/M-40	55	3.27°	05'00"	03'14"	02'18"	01'40"	04'14"	02'45"	02'54"	01'23"
R/M-55	55	3.27°	05'00"	03'14"	02'18"	01'40"	04'14"	02'45"	02'54"	01'23"
RW-55	55	6.55°	05'00"	03'14"	02'18"	01'40"	04'14"	02'45"	02'54"	01'23"
RVC-55	55	1.64°	05'00"	03'14"	02'18"	01'40"	04'14"	02'45"	02'54"	01'23"
RD-55	55	1.64°	05'00"	03'14"	02'18"	01'40"	04'14"	02'45"	02'54"	01'23"
RD-70	55	1.64°	05'00"	03'14"	02'18"	01'40"	04'14"	02'45"	02'54"	01'23"
BASIC40	55	3.27°	05'00"	03'14"	02'18"	01'40"	04'14"	02'45"	02'54"	01'23"
BRA	41	4.39°	03'44"	02'25"	01'43"	01'15"	03'09"	02'03"	02'09"	01'01"

Spritzkopf-Typ	Umdrehungen für kompletten Ablauf	Überlappung mit 2 Düsen / Spritzkopf	Druckluftmotor Typ Atlas Copco								
			1.5 bar 1.40 l/sec	2.0 bar 2.00 l/sec	2.5 bar 2.75 l/sec	3.0 bar 3.50 l/sec	3.5 bar 4.10 l/sec	4.0 bar 4.75 l/sec	4.5 bar 5.40 l/sec	5.0 bar 6.00 l/sec	
			7 min-1	9 min-1	10 min-1	12 min-1	13 min-1	14 min-1	15 min-1	16 min-1	
R-32	33	0.00°	00'00"	00'00"	00'00"	00'00"	00'00"	00'00"	00'00"	00'00"	00'00"
RK-37	37	5.45°	04'43"	03'40"	03'18"	02'45"	02'32"	02'21"	02'12"	02'04"	
R/M-40	55	4.86°	05'17"	04'07"	03'42"	03'05"	02'51"	02'39"	02'28"	02'19"	
R/M-55	55	3.27°	07'51"	06'07"	05'30"	04'35"	04'14"	03'56"	03'40"	03'26"	
RW-55	55	3.27°	07'51"	06'07"	05'30"	04'35"	04'14"	03'56"	03'40"	03'26"	
RD-55	55	1.64°	07'51"	06'07"	05'30"	04'35"	04'14"	03'56"	03'40"	03'26"	
RD-70	55	1.64°	07'51"	06'07"	05'30"	04'35"	04'14"	03'56"	03'40"	03'26"	
HPA	61	2.95°	07'51"	06'07"	05'30"	04'35"	04'14"	03'56"	03'40"	03'26"	

Spritzkopf-Typ	Umdrehungen für kompletten Ablauf	Überlappung mit 2 Düsen / Spritzkopf	Druckluftmotor Typ Fiam							
			1.5 bar 1.00 l/sec	2.0 bar 1.10 l/sec	2.5 bar 1.25 l/sec	3.0 bar 1.75 l/sec	3.5 bar 2.35 l/sec	4.0 bar 2.75 l/sec	4.5 bar 3.25 l/sec	5.0 bar 3.50 l/sec
			18 min-1	22 min-1	28 min-1	33 min-1	36 min-1	39 min-1	42 min-1	45 min-1
R-32	33	0.00°	00'00"	00'00"	00'00"	00'00"	00'00"	00'00"	00'00"	00'00"
RK-37	37	5.45°	01'50"	01'30"	01'11"	01'00"	00'55"	00'51"	00'47"	00'44"
R/M-40	55	4.86°	02'03"	01'41"	01'19"	01'07"	01'02"	00'57"	00'53"	00'49"
R/M-55	55	3.27°	03'03"	02'30"	01'58"	01'40"	01'32"	01'25"	01'19"	01'13"
RW-55	55	3.27°	03'03"	02'30"	01'58"	01'40"	01'32"	01'25"	01'19"	01'13"
RD-55	55	1.64°	03'03"	02'30"	01'58"	01'40"	01'32"	01'25"	01'19"	01'13"
RD-70	55	1.64°	03'03"	02'30"	01'58"	01'40"	01'32"	01'25"	01'19"	01'13"